

COMPANY	BRAND	APPLICATION	FIBER BLEND	BLEND RATIO	WEIGHT/ THICKNESS	FLAME	CHEMICAL	THERMAL	ABRASION	CUT	SPECIAL FEATURES
Bullard www.bullard.com	Isotherm Vest (ISO2)	Construction, confined space, DOT, more	FR cotton		~6 lbs. fully charged	x					Maintains 55-degree temp. for up to 4 hrs.
Bulwark Protective Apparel www.bulwark.com	Excel FR	Oil, gas, petroleum, utilities	Cotton	100	5.25 oz. - 14.75 oz.	x		x			Permanently treated for life of garment
	Nomex® IIA	Petroleum, refinery, utilities	Nomex®/Kevlar®/static dissipative fiber	93/5/2	4.5 oz - 7.5 oz.	x		x			Lightweight, breathable
	Excel FR Comfortouch	Utilities, oil, gas, petroleum	Cotton/nylon	88/12	7 oz. - 11.5 oz.	x		x			Comfortable, durable
	CoolTouch 2	Petroleum, electrical work	Modacrylic/Lyocell/Para-aramid	48/37/15	7 oz.	x		x			Ultra-lightweight, wickable
Magid Glove & Safety www.magidglove.com	SparkGuard®	Spark, flame protection	FR-treated cotton sateen	100	9 oz.-12 oz./yd ²	x		x			Flame resistant even after 50 washings; anti-static, more
	Lite N Kool®	Dust, grime, paint applications; cut/abrasion dangers	Spunbond polypropylene	100	1.25 oz./yd ²		x		x	x	Tear/puncture resistant, not liquid proof; choice of white, blue
	Lite N Kool® Plus	Dust, grime, paint applications; cut/abrasion dangers	3-layer SMS	100	60 grams		x		x	x	Barrier protection against particulates; abrasion resistant
	Poly Plus®	Dust, grime, paint applications; cut/abrasion dangers	Poly Plus® w/ polypropylene film	100	Medium		x		x	x	Snag/puncture resistant, liquid repellent, barrier protection
	DuPont™ Sontara®	Spark, flame protection	Sontara®	100	Medium	x					Made from heavier yet disposable, flame-resistant material

COMPANY	BRAND	APPLICATION	FIBER BLEND	BLEND RATIO	WEIGHT/ THICKNESS	FLAME	CHEMICAL	THERMAL	ABRASION	CUT	SPECIAL FEATURES
TenCate Protective Fabrics www.tencateprotectivefabrics.com	TenCate Tecasafe™ Plus	Electric arc, flash fire	FR modacrylic, Lyocell, aramid	48/37/15	7-8.5 OSY	x		x	x		Inherent FR protection, durable
	TenCate Freestyle™	Flash fire	Nomex®	100	4.5-7.5 OSY	x		x	x		Inherent FR protection, highly durable
	TenCate Oasis™	Molten metal splash	Lenzing FR® rayon, wool, nylon	50/40/10	7.5-12 OSY	x		x	x		Inherent FR protection, sheds metal
	TenCate Tuffweld®	Welding	Lenzing FR® rayon, para-aramid	60/40	8.5-10 OSY	x		x	x		Made for protection, strength, comfort
	TenCate Omniweave™	Flash fire	Nomex®	100	4.5-7.5 OSY	x		x	x		Inherent FR protection, highly durable*